
PRODUCT DATASHEET

Model: L4T527

Category: LED Tracklight Description: 31w LED Tunable White and Dimming with adjustable beam angle



Material: Aluminum Fitting Colors: Matte White/ Black/ Painted Silver Rotation Angle (degree): 355 Tilting Angle (degree): 90 Track System: 4 wires IP Rating: 20 Working Temperature (°C): -20 - +32 Storage Temperature (°C): -20 - +50




LIGHT DYNAMIC

Product Dimensions and Cut-out Information

Fitting Length (mm): 180-212.5 Diameter (mm): 85 Height (mm): Not Applicable Cut-out Dimension (mm): Not Applicable

Dimension:



Packing Information

Packaging Type: Individual box Quantity per carton: 12 CBM per carton: 0.08 Gross weight per carton (kgs): 14

Lifespan

Lifetime (hours): 50000 Luminous Flux after 50000hours (lm): LM80 Comply

PRODUCT DATASHEET

Model: L4T527

Category: LED Tracklight Description: 31w LED Tunable White and Dimming with adjustable beam angle



Light Technical Information

Color Temperature	CRI	System Lumen	Lumen per Watt
	(Ra)		
2700	90	2070	56
3000	90	2131	58
4000	90	2195	59
5000	90	2329	63
6500	90	2398	65

LED Manufacturer: Bridgelux LED Type: COB LED Model: BXRV-TR-2765G-30A0-A-23 Optic: Lens Beam Angle (°): 15-50

Electrical Information

System Power (w): 33 Input Voltage (v) & Frequency: 220-240V 50/60Hz Output Voltage (v): 32-35 Current (mA): 900 Non-dimmable: Rio driver with controller Power Factor: 0.95 Efficiency (%): 84 Total Harmonic Distortion (%): 20 Ripple (%): ±5 Dimming Range (%): 1-100