

PRODUCT DATASHEET

Model: LTC742

Category: LED Surface Mounted Spot Light

Description: 26w LED Surface Mounted Spot Light with Triac dimming



General Information

Material: Aluminum

Fitting Colors: White/ Black

Rotation Angle (degree): 350

Tilting Angle (degree): 60

Track System: Not Applicable

IP Rating: 20

Working Temperature (°C): -5 - +35

Storage Temperature (°C): -20 - +50



Product Dimensions and Cut-out Information


Fitting Length (mm): 217

Diameter (mm): 75

Height (mm): Not Applicable

Cut-out Dimension (mm): Not Applicable

Dimension:



Packing Information

Packaging Type: Individual box

Quantity per carton: 10

CBM per carton: 0.04

Lifespan

Lifetime (hours): 50000

Luminous Flux after 50000hours (lm): LM80 Comply

PRODUCT DATASHEET

Model: LTC742

Category: LED Surface Mounted Spot Light

Description: 26w LED Surface Mounted Spot Light with Triac dimming



Light Technical Information

Color Temperature	CRI (Ra)	Gamut Index (GAI)	System Lumen	Lumen per Watt
2700	90	90	1760	57
2700	95	100	1684	54
3000	90	90	1900	61
3000	95	100	1773	57
3000 Vivid White	90	110	1805	58
4000	90	90	2039	66
4000	95	100	1887	61
5000	80	90	2369	76
5000	90	90	2052	66

LED Manufacturer: Luminus

LED Type: COB

LED Model: CXM-9 Gen 3

Optic: Reflector

Beam Angle (°): 17/24/36

Electrical Information

System Power (w): 31

Input Voltage (v) & Frequency: 220-240V 50/60Hz

Output Voltage (v): 31-37

Current (mA): 700

Triac dimming: HEP LNTC30W700LRP

Power Factor: 0.9

Efficiency (%): 85

Total Harmonic Distortion (%): <20

Ripple (%): ±5

Dimmable: Dali Dimming – Upon Request

PRODUCT DATASHEET

Model: LTC742

Category: LED Surface Mounted Spot Light

Description: 26w LED Surface Mounted Spot Light with Triac dimming



Triac Dimmer

Manufacturer	Model
CLIPSAL	32E450UDM
TELLER	40200LED
CLIPSAL	32E450TM
PDL	654M
T&J	W2747
HYTEC	HY-L400DIM-T