

PRODUCT DATASHEET

Model: LXW103

Category: LED Recessed Linear Wall washer

Description: 54w LED Recessed Linear Wall washer



General Information

Material: Aluminum + Iron

Fitting Colors: Matte White/ Black

Rotation Angle (degree): Not Applicable

Tilting Angle (degree): Not Applicable

Track System: Not Applicable

Working Temperature (°C): -20 - +32

Storage Temperature (°C): -20 - +50



Product Dimensions and Cut-out Information



Fitting Length (mm): 51

Diameter (mm): 419 x 49

Height (mm): Not Applicable

Cut-out Dimension (mm): 405 x 36

Dimension:



Packing Information

Packaging Type: Individual box

Quantity per carton: 10

CBM per carton: 0.04

Gross weight per carton (kgs): Not Applicable

Lifespan

Lifetime (hours): 50000

Luminous Flux after 50000hours (lm): LM80 Comply

PRODUCT DATASHEET

Model: LXW103

Category: LED Recessed Linear Wall washer

Description: 54w LED Recessed Linear Wall washer



Light Technical Information

Color Temperature	CRI (Ra)	Gamut Index (GAI)	System Lumen	Lumen per Watt
2700	90	90	3242	54
2700	95	100	3000	50
3000	90	90	3394	57
3000	95	100	3151	53
4000	80	90	3606	60
4000	90	100	3333	56
5000	80	90	4242	71
5000	90	100	4242	71

LED Manufacturer: Luminus

LED Type: SMD

LED Model: 3030 6V

Optic: Reflector + Lens + Diffuser

Beam Angle (°): 66

Electrical Information

System Power (w): 60

Input Voltage (v) & Frequency: 220-240V 50/60Hz

Output Voltage (v): 34.4 – 37.6

Current (mA): 500

Non-Dimmable: Tridonic LC 60W 900-1750mA flexC SR EXC

Power Factor: 0.95

Efficiency (%): 90

Total Harmonic Distortion (%): <10

Ripple (%): ±5

Dimmable: Triac Dimming – Upon Request

1-10V Dimming – Upon Request

Dali Dimming – Upon Request