

# PRODUCT DATASHEET

**Model: L2T608 L3T608 L4T608**

Category: LED Tracklight

Description: 12w LED Tracklight



## General Information

Material: Aluminum

Fitting Colors: White/ Black/ Painted Silver

Rotation Angle (degree): 350

Tilting Angle (degree): 90

Track System: Available in single wire, 3 wire, 3 phase

IP Rating: 20

Working Temperature (°C): -5 - +35

Storage Temperature (°C): -20 - +50



## Product Dimensions and Cut-out Information


Fitting Length (mm): 142

Diameter (mm): 52

Height (mm): Not Applicable

Cut-out Dimension (mm): Not Applicable

Dimension:



## Packing Information

Packaging Type: Individual box

Quantity per carton: 10

CBM per carton: 0.036

Gross weight per carton (kgs): 10

## Lifespan

Lifetime (hours): 50000

Luminous Flux after 50000hours (lm): LM80 Comply

# PRODUCT DATASHEET

**Model: L2T608 L3T608 L4T608**

Category: LED Tracklight

Description: 12w LED Tracklight



## Light Technical Information

Color Temperature	CRI (Ra)	Gamut Index (GAI)	System Lumen	Lumen per Watt
2700	90	90	1037	69
2700	95	100	988	66
3000	90	90	1114	74
3000	95	100	1043	70
3000 Vivid White	90	110	1201	80
4000	95	100	1108	74
5000	80	90	1392	93
5000	90	90	1206	80

LED Manufacturer: Luminus

LED Type: COB

LED Model: CLM-9 Gen 3

Optic: Reflector

Beam Angle (°): 24/43/60

## Electrical Information

System Power (w): 15

Input Voltage (v) & Frequency: 220-240V 50/60Hz

Output Voltage (v): 31-37

Current (mA): 350

Non-Dimmable: LC 14W 350mA fixC R ADV

Power Factor: 0.9

Efficiency (%): 82

Total Harmonic Distortion (%): <9

Ripple (%): ±5

Dimmable: Triac Dimming – Upon Request

1-10V Dimming – Upon Request

Dali Dimming – Upon Request