### PRODUCT DATASHEET

Model: LTM514
Category: LED Tracklight
Description: 9w LED Tracklight



#### **General Information**

Material: Aluminum

Fitting Colors: White/ Black/ Painted Silver

Rotation Angle (degree): 350 Tilting Angle (degree): 60

Track System: Available in single wire, 3 wire

IP Rating: 20

Working Temperature (°C): -5 - +35 Storage Temperature (°C): -20 - +50



#### **Product Dimensions and Cut-out Information**


Fitting Length (mm): 80

Diameter (mm): 55

Height (mm): Not Applicable

Cut-out Dimension (mm): Not Applicable

#### Dimension:



# **Packing Information**

Packaging Type: Individual box

Quantity per carton: 20 CBM per carton: 0.0384

Gross weight per carton (kgs): 8.3

# Lifespan

Lifetime (hours): 30000

Luminous Flux after 50000hours (lm): LM80 Comply

### PRODUCT DATASHEET

**Model: LTM514**Category: LED Tracklight
Description: 9w LED Tracklight



# **Light Technical Information**

Color Temperature	CRI (Ra)	System Lumen	Lumen per Watt
3000	95	648	65

LED Manufacturer: Bridgelux

LED Type: COB

LED Model: BXKC-30H1501-D-13

Optic: Reflector

Beam Angle (°): 15/24/40/60

## **Electrical Information**

System Power (w): 10

Input Voltage (v) & Frequency: 220-240V 50/60Hz

Output Voltage (v): 16.2-19.6

Current (mA): 500

Non-Dimmable: RiO Non-dimmable Driver

Power Factor: 0.92 Efficiency (%): 85

Total Harmonic Distortion (%): <15

Ripple (%): ±3

Dimmable: Triac Dimming – Upon Request

1-10V Dimming – Upon Request Dali Dimming – Upon Request