

# PRODUCT DATASHEET

## Model: L4T738

Category: LED Tracklight

Description: 12-26W LED Tracklight



## General Information

Material: Aluminum

Fitting Colors: White/ Black/ Painted Silver

Rotation Angle (degree): 350

Tilting Angle (degree): 90

Track System: Available in 3 phase

IP Rating: 20

Working Temperature (°C): -5- +35

Storage Temperature (°C): -20 - +50



## Product Dimensions and Cut-out Information



Fitting Length (mm): 118

Diameter (mm): 85

Height (mm): Not Applicable

Cut-out Dimension (mm): Not Applicable

Dimension:



## Lifespan

Lifetime (hours): 30000

Luminous Flux after 30000hours (lm): LM80 Comply

# PRODUCT DATASHEET

## Model: L4T738

Category: LED Tracklight

Description: 12-26W LED Tracklight



## Light Technical Information

Color Temperature	CRI (Ra)	System Lumen (14 /18 /24 /29 W) (350 /450 /600 /700 mA)	Lumen per Watt (14 /18 /24 /29 W) (350 /450 /600 /700 mA)
2700	90	1616 /2055 /2667 /3135	115 /114 /110 /108
3000	90	1667 /2120 /2754 /3235	118 /117 /114 /112
3500	90	1778 /2267 /2965 /3505	126 /125 /123 /121
4000	90	1830 /2333 /3049 /3607	130 /129 /126 /124
5000	90	1830 /2333 /3049 /3607	130 /129 /126 /124

LED Manufacturer: TYF

LED Type: COB

LED Model: TX1 SERIES

Optic: Reflector

Beam Angle (°): 15/24/36

## Electrical Information

System Power (w): 14 /18 /24 /29

Input Voltage (v) & Frequency: 220-240V 50/60Hz

Output Voltage (v): 31-37

Current (mA): 350 /450 /600 /700 (DipSwitch)

Non-Dimmable: KGP SC30W SERIES

Power Factor: 0.75-0.95

Efficiency (%): 88

PstLM: ≤1

SVM: ≤0.4

Ripple (%): ±5

Dimmable: Dali Dimming – Upon Request

Default setting:

\* Current(mA): 450

\* System Power(w): 18

