


LLR12-CCT

7w LED Module With CCT Switchable



CCT Switchable



General Information

Housing Material:	Aluminium	Diffuser Material:	Frosted Glass
Colour (RAL):	Grey + Silver	Weight:	75g(Lamp)
Dimensions (L-W-H):	Dia.50mm – H45mm	Cuthole :	N/A
Connection:	AC Connector	Installation:	N/A
Rotation Angle:	N/A	Tilting Angle:	N/A
Temperature:	-20 ~ +35°C	Accessories:	N/A

Photometrical Data

LED Manufacturer:	TYF	LED Type:	COB
CCT:	2700K - 3000K(Mix) - 4000K	CRI(Minimum):	90
lm system (±5%):	588lm - 640lm - 633lm	lm source:	690lm - 752lm - 745lm
Luminous Efficiency:	73lm/w - 84lm/w - 79lm/w	MacAdam:	3
Optic:	Reflector	Beam Angle:	22°/43°/55°
UGR:	<19	LifeSpan (Ta25°C):	>50.000h - L70B50

Electrical Data

Driver:	LIFUD	Input Voltage:	220-240VAC 50/60Hz
Output Voltage:	25-42VDC	Output Current:	180mA
Power Factor:	>0.5	Current Ripple:	±5%
W system:	8.0W/7.6W/8.0W	Ballast Losses:	1.7W
Control:	ON/OFF	Minimum Dimming:	N/A
Inrush Current:	10A / 80µs	Max No. of Units	B10/13/16 = 60/-/96
		per MCB:	C10/13/16 = 100/-/160