



# [STELLAR] \_ LDL512

7w LED Small Hole Downlight

**RiO**  
LIGHT DYNAMIC



59



Ø75mm



## General Information

Housing Material:	Aluminium	Diffuser Material:	PC
Colour (RAL):	White(9016) - Black(9004)	Weight:	230g (lamp)
Dimensions (L-W-H):	Dia.85mm - H59mm	Cut hole :	75mm
Connection:	AC Connector	Installation:	Recessed Mounted
Rotation Angle:	N/A	Tilting Angle:	N/A
Temperature:	-20 ~ +35°C	Accessories:	N/A

## Photometrical Data

LED Manufacturer:	Luminus	LED Type:	CXM-4(G6)
CCT:	2700K - 3000K - 4000K	CRI(Minimum):	90
lm system (±5%):	477lm - 499lm - 525lm (#)	lm source:	723lm - 746lm - 786lm
Luminous Efficiency:	52lm/w - 55lm/w - 58lm/w	MacAdam:	3
Optic:	Lens + Anti-glare cover	Beam Angle:	26°/34°
UGR:	<8	LifeSpan (Ta25°C):	>50.000h - L70B50

## Electrical Data

Driver:	LIFUD	Input Voltage:	220-240VAC 50/60Hz
Output Voltage:	25-42VDC	Output Current:	200mA
Displacement Factor:	≥0.7	SVM & Pst:	≤0.4 & ≤1
W system:	9.1W	Ballast Losses:	1.9W
Control:	ON/OFF	Minimum Dimming:	N/A
Inrush Current:	10A / 80µs	Max No. of Units	B10/13/16 = 60/-/96
		per MCB:	C10/13/16 = 100/-/160

**Note:** # means the data is base on the 34° lens.