


# [STELLAR] \_ LDL513

10w LED Small Hole Downlight

**RiO**  
LIGHT DYNAMIC



62



Ø95mm



## General Information

Housing Material:	Aluminium	Diffuser Material:	PC
Colour (RAL):	White(9016) - Black(9004)	Weight:	361g (lamp)
Dimensions (L-W-H):	Dia.105mm – H62mm	Cut hole :	95mm
Connection:	AC Connector	Installation:	Recessed Mounted
Rotation Angle:	N/A	Tilting Angle:	N/A
Temperature:	-20 ~ +35°C	Accessories:	N/A

## Photometrical Data

LED Manufacturer:	Luminus	LED Type:	CXM-6(G6)
CCT:	2700K - 3000K - 4000K	CRI(Minimum):	90
lm system (±5%):	626lm - 652lm - 679lm (#)	lm source:	1252lm - 1299lm - 1355lm
Luminous Efficiency:	51lm/w - 53lm/w - 56lm/w	MacAdam:	3
Optic:	Lens + Anti-glare cover	Beam Angle:	27°/36°
UGR:	<10	LifeSpan (Ta25°C):	>50.000h - L70B50

## Electrical Data

Driver:	LIFUD	Input Voltage:	220-240VAC 50/60Hz
Output Voltage:	25-42VDC	Output Current:	300mA
Displacement Factor:	≥0.7	SVM & Pst:	≤0.4 & ≤1
W system:	12.4W	Ballast Losses:	2.0W
Control:	ON/OFF	Minimum Dimming:	N/A
Inrush Current:	9A / 120µs	Max No. of Units	B10/13/16 = 30/-/50
		per MCB:	C10/13/16 = 60/-/90

**Note:** # means the data is base on the 36° lens.